

ILULA®



ILULA LEVER HOIST

Robust & dependable lever hoist that is economical & lightweight

- Range from 750kg - 9,000kg
- Double pawl braking system
- Extra-thick asbestos-free friction plates
- **Anti-slip hooks providing extra safety with heavy duty cast safety latches**
- Time saving rapid free-wheeling system for fast hook-ups
- Full spares back-up for maintenance purposes
- Drop forged top & bottom hooks that can rotate 360°
- Designed to international standards. Generally compliant to SANS
- Units can be chained for any height of lift required
- **Overload protection available on request**
- Each unit is tested to 125% of the rated capacity
- **Serial numbered for traceability**
- **Supplied with individual test certificate**

Product Code	Capacity (ton)	Effort (kg)	Load Chain		Mass @ std 3m lift (kg)	Mass for extra metre HOL (kg)
			Diameter (mm)	No. of falls		
ILU075	0.75	14	6.0	1	8.0	0.9
ILU150	1.5	22	8.0	1	13.0	1.4
ILU300	3.0	32	10.0	1	22.0	2.2
ILU600	6.0	34	10.0	2	36.0	4.4
ILU900	9.0	36	10.0	3	53.0	6.6

OVERLOAD PROTECTION

Available on request

Factor of Safety 4:1

- Ilula 250kg Lever Hoist available with 1,5m load chain.
- Complete with carry bag
- Without overload protection



ASSEMBLED & TESTED IN SOUTH AFRICA