

# VITALIFT®



## CARBON STEEL HOOKS

Strong, durable hooks predominantly used in winching and hoisting.

- Forged from high-strength steel and heat treated
- Fatigue tested at 1,5 times working load limit
- Batch destruction testing
- 100% magnetic particle tested
- Factor of Safety 5:1


### EYE HOOK - HKEH



#### TECHNICAL SPECIFICATIONS

Product Code	Working Load Limit (t)	Breaking Load Limit (b)	D	E	H	K	M	L
HKEH00750	0,75	3,75	19	22	19	82	16	110
HKEH01000	1	5	23	23	21	93,5	17,5	125
HKEH01500	1,5	7,5	28	24	26	103	21	140,5
HKEH02000	2	10	31	27,5	28	119	23	162
HKEH03000	3	15	39	33	37	146	30	201
HKEH05000	5	25	51	40	46,5	186,5	38	256
HKEH07500	7,5	37,5	62	51	57	231,5	46	317
HKEH10000	11*	55	62	51	57	231,5	46	317
HKEH15000	15*	75	73	57	70	260	55	360

\*Alloy Steel - Factor of Safety 4:1




### SWIVEL HOOK - HKSW



#### TECHNICAL SPECIFICATIONS

Product Code	Working Load Limit (t)	A	E	B	H	K	L	M
HKSW00750	0,75	32,0	17,0	22,5	9,0	108,3	137,0	16,0
HKSW01000	1	37,5	22,5	29,5	12,0	133,5	163,5	16,0
HKSW01500	1,5	42,5	26,0	33,0	15,8	150,5	192,0	17,5
HKSW02000	2	42,5	.0	33,0	15,8	163,0	209,0	23,0
HKSW03000	3	48,0	32,5	39,0	18,0	191,0	246,0	31,0
HKSW05000	5	64,0	.0	53,0	25,0	243,5	313,0	34,0
HKSW07500	7,5	70,0	49,5	53,0	28,5	277,0	364,0	41,5
HKSW10000	11*	70,0	49,5	53,0	28,5	277,0	364,0	41,5
HKSW15000	15*	79,0	54,5	62,0	32,0	332,0	431,0	55,7

\*Alloy Steel - Factor of Safety 4:1




### SHANK HOOK - HKSH



#### TECHNICAL SPECIFICATIONS

Product Code	Working Load Limit (t)	B	E	C	M	G	F	D	L
HKSH0750	0,75	73,0	25,0	15,0	18,0	16,0	51,0	32,0	127,0
HKSH1000	1	80,3	25,5	16,7	20,0	18,0	58,0	35,0	147,0
HKSH1500	1,5	92,0	30,4	18,4	23,0	22,5	67,0	38,0	165,0
HKSH2000	2	105,0	32,0	22,4	26,0	24,0	69,0	41,4	177,5
HKSH3000	3	126,0	38,5	29,5	32,0	29,0	82,0	51,0	216,5
HKSH5000	5	167,0	47,0	35,8	40,0	36,0	95,5	64,0	262,5
HKSH7500	7,5	192,0	61,0	46,0	51,0	47,7	111,2	76,0	323,0
HKSH10000	10	214,6	66,0	50,8	55,6	55,5	114,0	82,5	342,0



### SLIDING CHOKER HOOK- HKSH



#### TECHNICAL SPECIFICATIONS

Product Code	Working Load Limit (t)	D	E	H	K	L
HKSC10/13	1,6	17,0	50,0	71,0	21,0	132,0
HKSC16	2,0	22,0	63,5	79,0	23,0	151,5
HKSC19	3,0	28,0	69,0	103,0	29,0	170,0
HKSC26	5,0	32,5	85,7	135,0	38,0	213,0

